

Application No. 10/697,574

Filed: October 30, 2003

TC Art Unit: 2652

Confirmation No.: 8327

THE CLAIMS

BEST AVAILABLE COPY

1. (Currently Amended) A disk drive, comprising:
 - a chassis case,
 - a disk tray capable of moving between a loading position inside the chassis case and an unloading position outside the chassis case while supporting a recording medium,
 - a bezel attached to the disk tray so as to cover a front end of the disk tray, and
 - an earth plate attached to a front end side of the disk tray to discharge static electricity; wherein
 - the static electricity generated at the front side of the disk tray is guided to the earth plate,
 - the disk tray has an earth plate attaching portion to which the earth plate is attached and a bezel attaching portion, separate from the earth plate attaching portion, to which the bezel is attached, and
 - the earth plate is attached directly to the earth plate attaching portion independently from the bezel, and the bezel is attached directly to the bezel attaching portion independently from the earth plate, wherein the earth plate remains fixed to the disk tray when the bezel is removed from the disk tray.
2. (Original) The disk drive according to claim 1, wherein the disk tray supports a supporting rotation means of a disk which rotates while supporting the disk.
3. (Original) The disk drive according to claim 1, further comprising an operating means to be operated when moving the disk

BEST AVAILABLE COPY

Application No. 10/697,574
Filed: October 30, 2003
TC Art Unit: 2652
Confirmation No.: 8327

tray located at the loading position toward the unloading position; wherein

the earth plate is set adjacently to the operating means.

4. (Original) The disk drive according to claim 1, further comprising an electrical displaying means for showing an operation state of the drive,; wherein

the earth plate is set adjacently to the electrical displaying means.

5. (Original) The disk drive according to claim 1, wherein the chassis case has conductivity,

the earth plate is electrically connected to the chassis case to supply static electricity generated at the front side of the disk tray to the chassis case when the disk tray is located at the loading position.

6. (Canceled)

7. (Original) The disk drive according to claim 1, wherein when the bezel is removed from the disk tray, the earth plate fixed to the disk tray so as to cover at least a part of the front end face of the disk tray is exposed to the front end of the disk tray.

8. (Previously Presented) The disk drive according to claim 1, the disk tray comprising the disk tray body and an inner bezel attached directly to the front end of the disk tray body, wherein

the earth plate is set between the disk tray body and the

Application No. 10/697,574

Filed: October 30, 2003

TC Art Unit: 2652

Confirmation No.: 8327

BEST AVAILABLE COPY

inner bezel, and

the bezel is attached to the front end of the disk tray so as to cover the inner bezel of the disk tray.

9. (Original) The disk drive according to claim 8, wherein the bezel formed like a plate is fixed to the inner bezel of the disk tray.

10. (Previously Presented) The disk drive according to claim 8, wherein the bezel formed like a shallow pan is fitted to the inner bezel of the disk tray.

11.-16. (Canceled)

17. (Currently Amended) A manufacturing method of a disk drive, comprising:

a chassis case,

a disk tray capable of moving between a loading position inside the chassis case and an unloading position outside the chassis case while supporting a recording medium,

a bezel attached to the disk tray so as to cover the front end of the disk tray, and

an earth plate set to the front end side of the disk tray to discharge static electricity, + comprising:

~~a step of integrating~~ the disk tray with the earth plate, and

~~a step of subsequently integrating~~ the bezel with the front end of the disk tray integrated with the earth plate.

18. (Original) The disk drive manufacturing method according to

BEST AVAILABLE COPY

Application No. 10/697,574

Filed: October 30, 2003

TC Art Unit: 2652

Confirmation No.: 8327

claim 17,

a disk tray comprising a disk tray body and an inner bezel attached to the front end of the disk tray body; wherein

the step of integrating the disk tray with the earth plate includes, a step of integrating the inner bezel with the earth plate and a step of integrating the inner bezel integrated with the earth plate with the disk tray body.

19. (Previously Presented) The disk drive according to claim 1, wherein the earth plate is attached to the disk tray body through an inner bezel by the earth plate being attached directly to the inner bezel and said inner bezel being attached to the disk tray body.